

Specifications

MODELS

Code	Interface
SB4A3042C261-00	CANbus - CANopen
SB4A3042M261-00	Serial - Modbus

POWER SUPPLY

Separated 24 Vdc (logic) and 18÷56 Vac (power)

POWER STAGE

H-bridge bipolar chopper of 40 KHz

CURRENT

0 ÷ 4.2 ARMS (0 ÷ 6.0 APEAK)

STEPLESS CONTROL TECHNOLOGY

65536 position per turn

OPTOISOLATED CONTROL INTERFACES

Serial RS485 or CANbus and SCI interface for programming and real time debugging

INPUTS / OUTPUTS

4 digital optocoupled inputs
2 digital optocoupled outputs (100 mA)
2 analog optocoupled inputs (potentiometer or ±10Vdc)

DIRECT FEEDBACK INTERFACE

5V TTL/CMOS for incremental encoder (not isolated)

SAFETY PROTECTIONS

Over Current, over Temperature, closed Windings phase/phase phase/ground

TEMPERATURE


Operating from 5°C to 40°C, storage from -25°C to 55°C
Humidity: 5%÷85% not condensed

Open loop / Closed Loop

Open Loop Control




Closed Loop Control



- with regard to an Open Loop Stepper Solution:
 - reliable positioning without synchronism loss;
 - keeps the original position stable and recovers it automatically in case of positioning errors caused by external factors such as mechanical vibrations;
 - 100% use of the motor torque;
 - capacity to operate at high velocity related to the current control, which is adjusted depending on the load variations, where the normal systems in open loop use a constant current control at all velocities without considering the load variations.
- compared with a brushless servo controlled solution:
 - no need to adjust the power (automatic current regulation depending on the load changes);
 - keeping the position stable without fluctuations after completing the positioning;
 - quick positioning favoured by the independent control of the integrated DSP;
 - continuous and fast execution of short stroke movements thanks to the short positioning time.

Full Digital Programmable Drive with fieldbus for Advanced Motion Control with reduced costs

TITANIO
VECTOR - STEPPER - DRIVES



error less servo efficient
else technology®
by Ever Elettronica

SB4A


Open frame

- Multiform Control Modes
- On Board Safety provisions:
 - ✓ fully tested for direct installation unit
 - ✓ built in watch dog functionality
 - ✓ fault monitoring and handling
 - ✓ on field working errors buffering
 - ✓ separated power supply for logic and power
- Servomotors main features:
 - ✓ Stepless control technology
 - ✓ low motor vibration
 - ✓ closed loop
 - ✓ low mechanical noise
 - ✓ AC power supply
 - ✓ PLC functionality
 - ✓ no resonance
 - ✓ high reliability
 - ✓ high speed and torque


Ever
ELETTRONICA
the clever drive

ELETTRONICA PER AUTOMAZIONE INDUSTRIALE
Via del Commercio, 2/4 -9/11
Loc. S. Grato - Z.I.
26900 - LODI (LO) - Italy
Tel. 0039 0371 412318 - Fax 0039 0371 412367
email infoever@everelettronica.it
www.everelettronica.it

Step & Direction or Analog



Multi Axes Systems




Stand Alone Mode


User Programmable - eePLC- c0490

eePLC integrates PLC, Motion Module, Process Module and drive in One Device. eePLC Studio PC interface is available to friendly, fast and easy custom to machine or process device programming.

Traditional Solution



eePLC - SM4A Solution



eePLC Handler allows user to access all the functionalities and resources of the device and to manage and synchronize the motion module and other drive resources to any process' events.


Access to all Powerful Motion functionalities

Built in **Process Real Time Modules** for special applications:


- Labelling
- Labelling Premium (c2490)
- CAM (c1390 and c1490)
- Wire Processing
- User Custom Process
-

Programmable for Stand-Alone functioning

Special Quick Configuration Windows for Process Realtime Modules.




Mechanical Data




Power Motion Module

- Step & Direction Control Mode
- Velocity Control Mode
- Wide range of Positioning Control Modes (homing, relative, absolute, target)
- CAM Mode... cam profile can be programmed
- Electric Gear with programmable gear ratio to track external master reference (from fieldbus or incremental encoder) of motor Speed and Position
- High speed I/O triggered motor start & stop to event synchronizing for fast response demanding application: labeling, nick_finder, on fly cut., etc ...
- Multi Axis movements synchronization capability
- On fly change among any Motion Module Control Modes
- On fly Electric Gear Enable/Disable capability
- Motor Stall detection & Target Position tracking through encoder feedback


Homing Motion Profiles



Mixed Motion Profiles



Multi Axes Synchronization



Ordering Information of SB4A open frame drives and options

Order code		Power			System Resources						
Versions	Config. (see table)	Power supply Power	Logic	Current	CAN	Serial	SCI	Digital Inputs	Digital Outputs	Analog Inputs	Encoder interface
SB4A3042C261-00	c0300 c0380 c0390 c1390	18 ÷ 56 Vac	24 Vdc	0 ÷ 4,2 A _{RMS} (0 ÷ 6,0 A _{PEAK})	CANbus (Canopen)	---	for programming and real time debug	4	2	2	1 5V TTL/CMOS
SB4A3042M261-00	c0400 c0490 c1490 c2490	18 ÷ 56 Vac	24 Vdc		---	RS485 (Modbus)					

Configuration, Control Method and Optional Software Starter Kits

Config.	Control	Software Starter Kits Code	Description of the Software Starter Kits
c0300	Canopen Control Mode	SB4A_SERV00-SL	Communication kit for SCI service interface to configure the drive with SL_Monitor.
c0380	Canopen Control Mode (CiA DS402 profile)		
c0390	Stand-Alone eePLC Studio IDE Canopen Mode		
c1390	Stand-Alone eePLC Studio IDE Canopen Mode with 'Electronic CAM'	SB4A_SERV00-EE	Communication kit for SCI service interface to program the drive with eePLC Studio IDE.
c0400	Modbus Control Mode	SB4A_SERV00-SL	Communication kit for SCI service interface to configure the drive with SL_Monitor.
c0490	Stand Alone eePLC Studio IDE Modbus Mode		
c1490	Stand-Alone eePLC Studio IDE Modbus Mode with 'Electronic CAM'		
c2490	Stand-Alone eePLC Studio IDE Mode with 'Labelling Premium'	SB4A_SERV00-EE	Communication kit for SCI service interface to program the drive with eePLC Studio IDE.